

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 342 541 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
10.09.2003 Bulletin 2003/37

(51) Int Cl.7: **B26B 21/22**

(21) Application number: 03012332.7

(22) Date of filing: 24.09.1998

(84) Designated Contracting States:
DE ES FR GB IT

(30) Priority: 30.09.1997 US 941328

(62) Document number(s) of the earlier application(s) in
accordance with Art. 76 EPC:
98948533.9 / 1 019 224

(71) Applicant: **THE GILLETTE COMPANY**
Boston, Massachusetts 02199 (US)

(72) Inventors:
• Apprille, Domenic Vincent Jr.
Arlington, MA 02174 (US)

• Anderson, Katherine Elizabeth
Swampscott, MA 01907 (US)

(74) Representative:
Ebner von Eschenbach, Jennifer et al
Ladas & Parry,
Dachauerstrasse 37
80335 München (DE)

Remarks:


This application was filed on 28 - 05 - 2003 as a
divisional application to the application mentioned
under INID code 62.

(54) **Razor cartridge with metal clip retaining blades**

(57) A razor cartridge characterized by a housing
having a wedge portion extending outward beyond an
adjacent portion, blades mounted on said housing, and

a metallic retaining clip that retains said blades and that
has an end portion that makes an interference fit with
said wedge portion so as to facilitate retaining said clip
on said housing.

FIG. 4



Description

[0001] The invention relates to razor cartridges having blades retained by metal clips.

[0002] In one type of movable-blade razor cartridge design, as shown for example in U.S. Patent No. 4,378,634, blades can move up and down in slots in a cartridge housing against resilient arms during shaving. Metal clips on the housing retain the blades in the slots and determine the positions of the cutting edges of the blades in the at-rest position. In manufacture, the blades are first loaded into the housing; then a U-shaped clip is positioned over the housing and blades, and the legs of the clip are bent around the bottom of the housing.

[0003] According to the present invention there is provided a razor cartridge characterized by a housing having a wedge portion extending outward beyond an adjacent portion, blades mounted on said housing, and a metallic retaining clip that retains said blades and that has an end portion that makes an interference fit with said wedge portion so as to facilitate retaining said clip on said housing.

[0004] According to a further aspect of the invention there is provided a method of assembling a razor cartridge, characterized by the steps of providing a housing having a wedge portion extending outward beyond an adjacent portion, locating blades on said housing, bending a U-shaped metallic retaining clip around said housing and blades located thereon beyond the elastic limit of said clip, and swaging said wedge portion over ends of said clip so as to make an interference fit of said wedge portion with said clip to retain said clip on said housing.

[0005] Certain implementations of the invention include one or more of the following features. In certain implementations there is a fulcrum portion for each of the two ends of the clip. The fulcrum portion tapers and has a blunt upper surface. The fulcrum portion is deformed and reduced in height by pressure applied to the fulcrum portion during bending of the clip over the fulcrum portion. The clip has a notch that is aligned with a notch post on the housing, and the clip bends at the fulcrum at a narrowed portion of the clip adjacent to the notch. The housing has a raised edge adjacent to an edge of the clip that positions the clip on the housing. The blades are movably mounted in slots in the housing. The blades are mounted on a top portion of the housing, and the ends of the clip are located at a bottom portion of the housing. The housing is recessed adjacent to the ends of the clip to receive the end portions of the clip during bending.

[0006] In another aspect, the invention features, in general a razor cartridge including a housing, blades mounted on the housing and a retaining clip. The housing has a wedge portion that extends outward beyond an adjacent portion and makes an interference fit with an end of the clip so as to facilitate retaining the clip on the housing.

[0007] In certain implementations, the housing has a raised edge adjacent to an edge of the clip that positions the clip on the housing, and the wedge portion extends sideways from the raised edge. The wedge portion has an angled surface at the interference fit, and the end portion of the clip has a mating angled surface. A portion of the wedge portion overlies a portion of the clip at the interference fit.

[0008] In other aspects the invention features housings as already described for use in razor cartridges and methods of assembling razor cartridges using the housings and clips as already described.

[0009] Embodiments of the invention may have one or more of the following advantages. The use of fulcrum portions and wedge portions permits longer clips to be used and thicker clip material to be used without having the end portions of the clips spring back to too large an extent after forming. The longer and thicker clips facilitate use on cartridge housings that have been made wider in order to accommodate a third blade.

[0010] Other advantages and features of the invention will be apparent from the following description of the preferred embodiment thereof and from the claims.

Fig. 1 is a perspective view of a razor according to the invention.

Fig. 2 is an exploded perspective view of a blade unit of the Fig. 1 razor.

Fig. 3 is a partial bottom view of the Fig. 2 blade unit.

Fig. 4 is a vertical sectional view, taken at 4-4 of Fig. 3, of a housing of the Fig. 2 blade unit.

Fig. 5 is a vertical sectional view, taken at A-A of Fig. 3, of the Fig. 4 cartridge housing.

Fig. 6 is a partial vertical sectional view showing a forming die used to bend retaining clips around the Fig. 4 cartridge housing.

Figs. 7, 8, and 9 are vertical sectional views, taken at A-A of Fig. 3, showing the Fig. 4 housing and a retaining clip at three different stages during the assembly of the clip on the housing.

Fig. 10 is a vertical sectional view, taken at A-A of Fig. 3, of the assembled Fig. 2 blade unit with the ends of the retaining clip in a desired final position.

Fig. 11 is a partial vertical sectional view, taken at 11-11 of Fig. 10, showing the interference fit and overlying contact of a wedge portion of the housing and the retaining clip.

[0011] Referring to Fig. 1, shaving razor 10 includes handle 12 and replaceable shaving cartridge 14. Cartridge 14 includes molded plastic housing 16, which carries three blades 18, guard 20 and cap 22. Cartridge 14 also includes plastic interconnect member 24 on which housing 16 is pivotally mounted. Interconnect member 24 removably and fixedly attaches to handle 12 and has two arms 26 that pivotally support housing 16 at its two sides. Cartridge 14 is shown in its spring-biased, upward position in Fig. 1.

[0012] Referring to Fig. 2, housing 16 of cartridge 14 has inwardly facing slots 28 in side walls 30 for receiving the ends of base portions 32 of blades 18. Housing 16 also has respective pairs of resilient arms 36 on which each blade 18 is resiliently supported. Blades 18 are located in a substantially unobstructed region 38 between side walls 30 to provide for ease of rinsing of the cartridge during use.

[0013] Cap 22 provides a lubricous shaving aid and is received in slot 40 at the rear of housing 16. Cap 22 may be made of a material comprising a mixture of a hydrophobic material and a water leachable hydrophilic polymer material, as is known in the art and is described, e.g., in U.S. Patents Nos. 5,113,585 and 5,454,164, which are hereby incorporated by reference. Guard 20 includes a finned elastomeric unit molded on the front of housing 16 to engage and stretch the user's skin; other skin engaging protrusions, e.g., as described in U.S. Patent No. 5,191,712, which is hereby incorporated by reference, can be used.

[0014] Metal clips 42 are secured at the respective sides of housing 16 inside of raised edges 44 of side walls 30 in order to retain blades 18 within housing 16 and to locate the cutting edges of spring-biased blades 18 at a desired exposure when in the at-rest position. Clips 42 also wrap around the bottom of housing 16 and prevent the removal of the ends of arms 26 of interconnect member 24. Clips 42 are made of 0.018" thick aluminum material, which is thicker than the material used in the clips of the blade unit of the commercial embodiment of the type of design described in the above-mentioned U.S. Patent No. 4,378,634. In addition, the arms of the clips that are bent around the bottom of housing 16 are both longer than those employed in the commercial embodiment of the type of design described in the above-mentioned patent, because there are three blades (instead of two) and the housing thus is wider. The thicker material and the longer arms to be bent cause the arms to tend to elastically return to a larger extent after forces bending the clips around the housing have been released. Housing 16 includes certain features (described below) to maintain the thicker, longer clips in a desired final position.

[0015] Referring to Fig. 3, it is seen that the end portions 50 of clips 42 have notches 52 that are aligned with notch posts 54 (see also Fig. 4) of housing 14. It is also seen that housing 16 has wedge portions 56 that extend in from raised edges 44 and have angled surfaces 58 that contact angled surfaces 60 of end portions 50 of clips 42. Wedge portions 56 (see also Fig. 4) and the contacting surfaces 60 of clips 42 make an interference fit in order to help retain the ends of clips 42 on housing 16.

[0016] Referring to Figs. 4 and 5, it is seen that housing 16 has fulcrums 62 that extend outward beyond the adjacent surface portions of housing 16 on both sides of fulcrums 62. As shown in Fig. 5, fulcrums 62 have a semicircular cross-section and therefore are tapered

and have a blunt upper surface.

[0017] In manufacture, blades 18 are located on housing 16 by inserting the ends of base portions 32 in slots 28 and depressing the blades downward against resilient arms 36. Prior to assembly, retaining clips 42 are U-shaped, and the portion of the U that joins the two legs has the same contour as the upper portion of housing 16 within raised edges 44. The upper portions of the preassembled clips 42 thus have the same shape of the upper portions of clips 42 as shown in Fig. 2. Prior to assembly, the two legs of the U-shaped clip (which legs correspond to portions 66, 68 in Fig. 2) are directed straight downward and parallel to each other, and leg 66 is shorter than leg 68.

[0018] The clip/housing/blade assembly (with the upper portion of clips 42 seated on housing 16 inside of raised edges 44) is directed downward against forming die 100 shown in Fig. 6. Surfaces 102, 104 of die 100 deflect legs 66 and 68 inward as the housing/blade/clip assembly is brought closer to die 100. This causes the legs 66, 68 of clip 42 to initially bend around the bottom of housing 16 to the position shown in Fig. 7. At this stage in the forming process, the end portions 50 of legs 66, 68 have just made initial contact with fulcrums 62. (In Figs. 7-10, the base portions 32 of blades 18 and the ends of arms 26 are not shown on housing 16, though they are present during these stages of the manufacturing process and in the final assembly.)

[0019] Referring to Fig. 8, with further advancement of the housing/blade/clip assembly toward die 100, the end portions 50 of the clips 42 tend to bend around fulcrums 62 at regions nearby notches 52 where clips 42 are thinner. Simultaneously with bending of clips 42 around fulcrums 62, fulcrums 62 begin to be crushed from the resulting forces, and the crushed material of fulcrums 62 is directed toward recess 72. At the same time, angled surfaces 60 of clips 42 move past angled surfaces 58 of wedge portions 56 (Fig. 3), and notches 52 begin to pass over notch posts 54 (Figs. 3, 4).

[0020] Referring to Fig. 9, further advancement of the housing/blade/clip assembly toward the forming die causes the ends 70 of the clips to contact the bottom of recess 72 of housing 16 in the position of their most deflected travel. At this point, fulcrums 62 have been crushed flat, with displaced material in recess 72, and ends 50 have been permanently bent beyond the elastic limit of the clip material at the regions of the clips overlying fulcrums 62. At the same time, angled surfaces 60 of clips 42 travel further over angled surfaces 58 of wedge portions 56 (Fig. 3), and the tops of wedge portions 56 are deformed (i.e., swaged) by projection 106 of forming die 100, causing displaced wedge material to slightly overlie the ends of clips 42 and to create an interference fit that exerts a normal spring force against wedge portions 56.

[0021] When the housing/blade/clip assembly is removed from forming die 100, the ends 50 tend to elastically return slightly to the position shown in Figs. 10


and 11, though such movement is inhibited by the swaged plastic of wedges 56.

[0022] The interference fit between angled clip surfaces 60 and angled wedge surfaces 58 and the overlying swaged material (as shown in Fig. 11) tend to hold the ends of the clips 42 in place and to inhibit them from moving outward from housing 16. Also, notches 52 of clips 42 receive notch posts 54, causing end portions 50 of clips 42 to be captured between projections 42 and wedge portion surfaces 58 and to inhibit clip 42 from opening up during use, e.g., when the cartridge is subjected to excessive forces as might arise when the cartridge is dropped.

Claims

1. A razor cartridge **characterized by** a housing having a wedge portion extending outward beyond an adjacent portion, blades mounted on said housing, and a metallic retaining clip that retains said blades and that has an end portion that makes an interference fit with said wedge portion so as to facilitate retaining said clip on said housing.
2. A cartridge according to claim 1, **characterized in that** the housing has a raised edge adjacent to an edge of the clip that positions said clip on said housing, and **in that** the wedge portion extends sideways from said raised edge.
3. A cartridge according to claim 1, **characterized in that** the wedge portion has an angled surface at said interference fit, and said end portion of said clip has a mating angled surface.
4. A cartridge according to claim 1, **characterized in that** the end portion of the clip has a notch.
5. A cartridge according to claim 4, **characterized in that** the housing a notch post aligned with said notch.
6. A cartridge according to claim 1, **characterized in that** a portion of the wedge portion overlies a portion of the clip at said interference fit.
7. A cartridge according to claim 1, **characterized in that** the wedge portion is swaged over the ends of said clip, and **in that** the housing is recessed inward at a portion of said housing adjacent to the ends of said clip to receive said end portions of said clip during swaging of said wedge portion.
8. A method of assembling a razor cartridge, **characterized by** the steps of providing a housing having a wedge portion extending outward beyond an adjacent portion, locating blades on said housing, bending a U-shaped metallic retaining clip around said housing and blades located thereon beyond the elastic limit of said clip, and swaging said wedge portion over ends of said clip so as to make an interference fit of said wedge portion with said clip to retain said clip on said housing.
9. A method according to claim 8, **characterized in that** the housing has a raised edge adjacent to an edge of said clip that positions said clip on said housing.
10. A method according to claim 8, **characterized in that** the housing is recessed at a portion of said housing adjacent to the ends of said clip to receive end portions of said clip during said bending and said swaging.

FIG. 1






FIG. 3





FIG. 4






FIG. 5




FIG. 6

FIG. 7




FIG. 8




FIG. 9




FIG. 10





FIG. 11



(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 342 541 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
17.09.2003 Bulletin 2003/38

(51) Int Cl.7: **B26B 21/22**

(43) Date of publication A2:
10.09.2003 Bulletin 2003/37

(21) Application number: 03012332.7

(22) Date of filing: 24.09.1998

(84) Designated Contracting States:
DE ES FR GB IT

(30) Priority: 30.09.1997 US 941328

(62) Document number(s) of the earlier application(s) in
accordance with Art. 76 EPC:
98948533.9 / 1 019 224

(71) Applicant: **THE GILLETTE COMPANY**
Boston, Massachusetts 02199 (US)

(72) Inventors:

- Apprille, Domenic Vincent Jr.
Arlington, MA 02174 (US)
- Anderson, Katherine Elizabeth
Swampscott, MA 01907 (US)

(74) Representative:


Ebner von Eschenbach, Jennifer et al
Ladas & Parry,
Dachauerstrasse 37
80335 München (DE)

(54) **Razor cartridge with metal clip retaining blades**

(57) A razor cartridge characterized by a housing having a wedge portion(56) extending outward beyond an adjacent portion, blades mounted on said housing,

and a metallic retaining clip (42) that retains said blades and that has an end portion (50) that makes an interference fit with said wedge portion so as to facilitate retaining said clip on said housing.

FIG. 4





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 03 01 2332

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	WO 96 10473 A (GILLETTE CO ;ANDERSON KATHERINE (US); MAIDER RALPH KENNETH JR (US)) 11 April 1996 (1996-04-11) * page 5, line 13 - page 9, line 26; figures 1-10 *	1,8	B26B21/22
A	US 4 492 024 A (JACOBSON CHESTER F) 8 January 1985 (1985-01-08) * column 2, line 49 - column 3, line 57; figures 1-4 *	1,8	
D,A	US 4 378 634 A (JACOBSON CHESTER F) 5 April 1983 (1983-04-05) * the whole document *	1,8	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			B26B
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 18 July 2003	Examiner Herijgers, J
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 03 01 2332

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

18-07-2003

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9610473	A	11-04-1996	AT 186489 T	15-11-1999
			AU 703762 B2	01-04-1999
			AU 3828795 A	26-04-1996
			BR 9509216 A	27-01-1998
			CA 2200720 A1	11-04-1996
			CN 1159779 A	17-09-1997
			CZ 9700931 A3	17-09-1997
			DE 69513302 D1	16-12-1999
			DE 69513302 T2	08-06-2000
			DK 784530 T3	01-05-2000
			EP 0784530 A1	23-07-1997
			ES 2138241 T3	01-01-2000
			FI 971357 A	02-04-1997
			GR 3032495 T3	31-05-2000
			HK 1001517 A1	14-07-2000
			JP 10506813 T	07-07-1998
			NZ 295038 A	29-03-1999
			PL 319452 A1	04-08-1997
			PT 784530 T	28-04-2000
			RU 2131349 C1	10-06-1999
			TR 960280 A2	21-06-1996
			WO 9610473 A1	11-04-1996
			US 5761814 A	09-06-1998
US 4492024	A	08-01-1985	CA 1209327 A1	12-08-1986
			US 4498235 A	12-02-1985
			US 4621424 A	11-11-1986
			US 4573266 A	04-03-1986
US 4378634	A	05-04-1983	US 4270268 A	02-06-1981
			AU 537273 B1	14-06-1984
			BR 8200326 A	23-11-1982
			CA 1150492 A1	26-07-1983
			DE 3127999 A1	12-08-1982
			ES 271894 Y	16-04-1984
			FR 2498971 A1	06-08-1982
			GB 2092052 A	11-08-1982
			GR 76358 A1	06-08-1984
			IT 1150135 B	10-12-1986
			JP 57148979 A	14-09-1982
			NL 8200238 A	16-08-1982
			US 4442598 A	17-04-1984
			AR 230807 A1	31-07-1984
			AU 528451 B2	28-04-1983
			BR 8007772 A	16-06-1981
			CA 1130997 A1	07-09-1982

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 03 01 2332

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

18-07-2003

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4378634 A	DE	3042671 A1	11-06-1981
	ES	259039 Y	01-11-1982
	ES	8200257 A1	16-01-1982
	FR	2471260 A1	19-06-1981
	GB	2064410 A ,B	17-06-1981
	GR	71616 A1	17-06-1983
	HK	33583 A	09-09-1983
	IN	155035 A1	22-12-1984
	IT	1127929 B	28-05-1986
	JP	1237349 C	31-10-1984
	JP	56132983 A	17-10-1981
	JP	59013875 B	02-04-1984
	NL	8006527 A ,B,	01-07-1981
	US	4378633 A	05-04-1983
